SDC 8000 ID

Conference and Information Systems | SDC 8000

Cat. No. 009418

General Description

Designed according to international standards, the SDC 8000 ID interpreter unit is an ideal choice for large, international conferences with up to 28 translated languages and up to eight interpreter units per booth. The SDC 8000 ID is extremely easy to use. All important information and settings are shown on a back-lit graphic LCD display. The incoming languages can be chosen via three configurable relais keys. A language quality indicator marks the language which has been translated several times, thus avoiding possible information loss.

Technical Data

Frequency response	100 – 14,000 Hz
Pick-up pattern	cardioid
Headphone connector	3.5 mm mono (> 32 Ω)
Power supply	48 V DC
Power consumption	max. 4 W
Operating temperature	0 – 50 °C
Standards	ISO 2603; IEC 849
Colour	Pantone Black 7C
Housing	ABS
Dimensions	150 x 80 x 185 mm
Gooseneck length	380 mm
Weight	675 g

Features

- Gooseneck microphone with red LED ring
- Two 3.5 mm headphone jacks
- Two RJ 45 sockets for connecting up to 15 units in one cable line
- Three tone controls for volume, mid-range and treble
- Built-in high-quality loudspeaker (automatically muted when a microphone in the booth is switched on)
- Loudspeaker volume control
- Loudspeaker channel selection for incoming language
- Three configurable relais keys for incoming languages
- Two A and B output channels, channel selection key and "ENGAGED" LEDs
- Configurable B channel
- Back-lit graphic LCD display for relay languages, quality of relay languages, loudspeaker language, set-up mode (only during basic configuration)
- Large, red MIC key with LED
- Mute key
- Message keys with LED for displaying text messages
- Delivery includes: 1 SDC 8000 ID Interpreter Unit

Accessories

- RJ 45 conference bus cables, type 24 AWG, available lengths: 2 m, 3 m, 5 m, 10 m, 20 m, 50 m
- HD 410-D, HD 1029 headphones